NSN 6625-00-585-5353

Ammeter - Page 1 of 2

3000.0

Overall Length: 2.067 inches

Scale Division Quantity: 5 single indicator single range

Circuit Current For Which Designed:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-585-5353

| Mounting Stud Length: |
|--|
| 0.870 inches |
| Overall Diameter: |
| 2.695 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 20000.0 ohms per volt |
| Dial Scale Marking Color: |
| Yellow single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.687 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.210 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| Black single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 3 threaded stud |
| Scale Graduation Type: |
| Linear single indicator single range |
| Measurement Range: |
| +0.0/+500.0 milliamperes, dc single indicator single range |

NSN 6625-00-585-5353

Ammeter - Page 2 of 2



| Mounting Stud Diameter: |
|---|
| 0.112 inches |
| Scale Selection Method: |
| Terminal |
| Features Provided: |
| Zero adjuster |
| Circuit Attachment Method And Quantity: |
| 2 solderless lug |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, electronic equipment |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Filg: |
| A310a0 |
| |