

View Online at <https://aerobasegroup.com/nsn/6625-00-585-5490>

Circuit Current For Which Designed:

Ac

Overall Length:

3.727 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

65 single indicator single range

Overall Diameter:

3.500 inches

Mounting Bolt Circle Diameter:

1.578 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Frequency Response Range:

+0.000 to 60.000 hertz

Sensitivity Rating:

1.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.0 to 1.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

3.718 inches

Meter Body Diameter Behind Mounting Flange:

2.671 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+100.0 to 130.0 volts, ac single indicator single range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 solder stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0