NSN 6625-00-585-5665

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-585-5665

Overall Length:
9.750 inches
Overall Height:
13.500 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 60.0 hertz
Accessory Components And Quantity:
1 ea p410 attenuator probe, 2 ea a510 binding post adapters, 1 ea green filter (378-514), 1 ea instruction manual
Voltage Rating:
Between 105.0 volts and 250.0 volts
Beam Quantity:
1
Screen Size:
5 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Single Trigger Sweep Duration:
Between 0.2 microseconds and 2000000.0 microseconds
Trigger Sweep Voltage Amplitude Rating:
100.0 volts
Trigger Sweep Polarity Switch:
Included
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
0.05 volts rms per centimeter and 20.00 volts rms per centimeter
Horizontal Deflection Sensitivity Voltage Rating:
1.4 volts any acceptable minor
Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Not provided
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:

500.0 kilohertz

NSN 6625-00-585-5665

Oscilloscope - Page 2 of 2



Y-axis Frequency Response Rating:
150.0 megahertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
T320-g