

View Online at <https://aerobasegroup.com/nsn/6625-00-585-5665>

**Overall Length:**

9.750 inches

**Overall Height:**

13.500 inches

**Current Type:**

Ac

**Frequency Rating:**

Between 50.0 hertz and 60.0 hertz

**Accessory Components And Quantity:**

1 ea p410 attenuator probe, 2 ea a510 binding post adapters, 1 ea green filter (378-514), 1 ea instruction manual

**Voltage Rating:**

Between 105.0 volts and 250.0 volts

**Beam Quantity:**

1

**Screen Size:**

5 in.

**Sweep Circuits:**

Included

**Generator Driven Feature:**

Not included

**Single Trigger Sweep Duration:**

Between 0.2 microseconds and 2000000.0 microseconds

**Trigger Sweep Voltage Amplitude Rating:**

100.0 volts

**Trigger Sweep Polarity Switch:**

Included

**Expanded Sweep:**

Not provided

**Amplifier Deflection Sensitivity Provision:**

Provided

**Vertical Deflection Sensitivity Voltage Rating:**

0.05 volts rms per centimeter and 20.00 volts rms per centimeter

**Horizontal Deflection Sensitivity Voltage Rating:**

1.4 volts any acceptable minor

**Input Intensity Modulation Feature:**

Not provided

**Plate Direct Connection Deflection Sensitivity Provision:**

Not provided

**Frequency Response Rating:**

Provided

**X-axis Frequency Response Rating:**

500.0 kilohertz

**Y-axis Frequency Response Rating:**

150.0 megahertz

**Amplifier Input Impedance Rating Provision:**

Provided

**X-axis Input Impedance Rating:**

1.0 megohms

**Y-axis Input Impedance Rating:**

1.0 megohms

**Calibrated Screen Scale:**

Not included

**Trace Storage Tube:**

Not included

**Camera Recording Device Accommodation:**

Not provided

**Phase:**

Single

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

T320-g