

View Online at <https://aerobasegroup.com/nsn/6625-00-585-5947>

Circuit Current For Which Designed:

Ac

Overall Length:

2.002 inches

Mounting Hole Diameter:

0.120 inches

Overall Diameter:

2.685 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

2.488 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black and red single indicator 1st range

Accuracy In Percent:

-10.0 to 10.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.141 inches

Meter Body Diameter Behind Mounting Flange:

2.072 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

-20.0 to 3.0 voice units single indicator 1st range

Features Provided:

Zero adjuster

Circuit Attachment Method And Quantity:

2 solder lug

Special Features:

Ruggedized

Special Markings:

Top scale: red band 0 to 3

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0