NSN 6625-00-591-2238

Ammeter - Page 1 of 2

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-591-2238

Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
1.750 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
41 single indicator single range
Overall Diameter:
2.695 inches
Environmental Protection:
Dustproof
Mounting Bolt Circle Diameter:
2.440 inches
Furnished Items And Quantity:
Mtg screws w/nuts and lockwashers 3
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
g /go
Three hole/stud bolt circle
Three hole/stud bolt circle
Three hole/stud bolt circle Sensitivity Rating:
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color:
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent:
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange:
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.500 inches
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.500 inches Meter Body Diameter Behind Mounting Flange:
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.500 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.500 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type:
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.500 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.500 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color:
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.500 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range
Three hole/stud bolt circle Sensitivity Rating: 150.0 millivolts Dial Scale Marking Color: Black single indicator single range Accuracy In Percent: -2.0/+2.0 at full scale single indicator single range Meter Depth Behind Mounting Flange: 1.500 inches Meter Body Diameter Behind Mounting Flange: 2.210 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator single range Pointer Color:

NSN 6625-00-591-2238

Ammeter - Page 2 of 2



Scale Graduation Type:
Linear single indicator single range
Measurement Range:
-1.0/+1.0 milliamperes, dc single indicator single range
Scale Selection Method:
Switch
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Markings:
Milliamperes dc on face of dial scale
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0