

View Online at <https://aerobasegroup.com/nsn/6625-00-594-0320>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.093 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.604 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.290 inches

Overall Height:

2.950 inches

Overall Width:

4.259 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

End Application:

Forrestal class cv, iwo jima class lph, ticonderoga class cg (47), yellowstone class ad-41, wasp class lhd, nimitz class cvn

Furnished Items And Quantity:

Shunt wire 1; nut 6; lockwasher 6; seal 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Dial Scale Marking Color:

Black and green single indicator all ranges

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

0.993 inches

Meter Body Diameter Behind Mounting Flange:

3.263 inches

Movement Type:

Moving iron vane

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Scale Graduation Type:

Nonlinear single indicator all ranges

Measurement Range:

+0.0 to 0.5 decibels single indicator 1st range

Scale Selection Method:

Terminal

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized

Special Markings:

On front, output; volts

Material:

Steel

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0