

View Online at <https://aerobasegroup.com/nsn/6625-00-594-0525>

Circuit Current For Which Designed:

Ac

Overall Length:

2.051 inches

Mounting Hole Diameter:

0.129 inches

Overall Diameter:

2.697 inches

Environmental Protection:

Shock resistant and vibration resistant

Mounting Bolt Circle Diameter:

2.438 inches

End Application:

Austin ship class lpd-4 amphibious transport docks, sturgeon class ssn (637), ticonderoga class cg (47), emory s. Land class as, general purpose electronic test equipment gpete

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Dial Scale Marking Color:

Black and red single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.390 inches

Meter Body Diameter Behind Mounting Flange:

2.170 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Red single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator single range

Measurement Range:

-6.0 to 3.0 decibels above or below one milliwatt single indicator single range

Features Provided:

External shunting and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 turret

Special Features:

Ruggedized

Material:

Plastic

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A310a0