

View Online at <https://aerobasegroup.com/nsn/6625-00-596-0484>

**Circuit Current For Which Designed:**

Dc

**Overall Length:**

2.860 inches

**Scale Division Quantity:**

6 single indicator single range

**Overall Diameter:**

2.280 inches

**Environmental Protection:**

Dustproof and waterproof

**Furnished Items And Quantity:**

Clamp 1

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Sensitivity Rating:**

56.0 milliamperes

**Dial Scale Marking Color:**

White single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.520 inches

**Meter Body Diameter Behind Mounting Flange:**

2.060 inches

**Movement Type:**

Moving iron vane

**Background Color:**

Black single indicator single range

**Pointer Color:**

Black and orange single indicator single range

**Power Source:**

External

**Mounting Facility Type And Quantity:**

2 clamp

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+10.0 to 16.0 volts, dc single indicator single range

**Scale Selection Method:**

Terminal

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Operating Voltage Rating In Volts:**

12.0 dc

**Special Features:**

Ruggedized

**Special Markings:**

Batt above left side scale; chge above right; red band at 10.0 to 11.3 and at 15.3 to 16; yellow band at 11.3 to 12.0; green band at 12.0 to 15.3

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Round flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0