

View Online at <https://aerobasegroup.com/nsn/6625-00-596-0484>

Circuit Current For Which Designed:

Dc

Overall Length:

2.860 inches

Scale Division Quantity:

6 single indicator single range

Overall Diameter:

2.280 inches

Environmental Protection:

Dustproof and waterproof

Furnished Items And Quantity:

Clamp 1

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Sensitivity Rating:

56.0 milliamperes

Dial Scale Marking Color:

White single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.520 inches

Meter Body Diameter Behind Mounting Flange:

2.060 inches

Movement Type:

Moving iron vane

Background Color:

Black single indicator single range

Pointer Color:

Black and orange single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

2 clamp

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+10.0 to 16.0 volts, dc single indicator single range

Scale Selection Method:

Terminal

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Operating Voltage Rating In Volts:

12.0 dc

Special Features:

Ruggedized

Special Markings:

Batt above left side scale; chge above right; red band at 10.0 to 11.3 and at 15.3 to 16; yellow band at 11.3 to 12.0; green band at 12.0 to 15.3

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0