

View Online at <https://aerobasegroup.com/nsn/6625-00-601-6089>

Circuit Current For Which Designed:

Ac

Dielectric Withstanding Voltage In Volts:

800.0

Overall Length:

2.968 inches

Mounting Hole Diameter:

0.150 inches

Frequency Rating:

Between 47.0 hertz and 63.0 hertz

Overall Diameter:

3.500 inches

Environmental Protection:

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 3; lockwasher 3; seal 1

Indicator Type:

Vibrating reed

Installation Design:

Panel

Register Quantity:

2

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

140.0 ohms per volt

Dial Scale Marking Color:

Black single indicator all ranges

Resonant Reed Quantity:

14

Accuracy In Percent:

-3.0 to 3.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

2.250 inches

Meter Body Diameter Behind Mounting Flange:

2.687 inches

Movement Type:

Vibrating reed

Background Color:

White single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Measurement Range:

+57.0 to 63.0 hertz single indicator 2nd range

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield

Circuit Attachment Method And Quantity:

2 eyelet

Operating Voltage Rating In Volts:

Between 100.0 ac and 130.0 ac

Special Features:

Ruggedized

Special Markings:

On side, sealed do not open

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Paint

Special Test Features:

Complies with mil-m-10304

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0