# NSN 6625-00-604-9573

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-604-9573

# Circuit Current For Which Designed: Dc Dielectric Withstanding Voltage In Volts: 3000.0

### **Overall Length:**

2.001 inches

# Mounting Hole Diameter:

0.125 inches

#### Scale Division Quantity:

20 single indicator all ranges

#### **Overall Diameter:**

2.695 inches

#### **Environmental Protection:**

Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and water resistant

# Mounting Bolt Circle Diameter:

2.440 inches

# Furnished Items And Quantity:

Nut 3; lockwasher 3; seal 2; face plate 1

### Indicator Type:

Dial w/pointer

#### Installation Design:

Panel

#### Mounting Arrangement Style:

Three hole/stud bolt circle

### Sensitivity Rating:

50.0 microamperes

# **Dial Scale Marking Color:**

Black single indicator all ranges and white single indicator all ranges

#### Accuracy In Percent:

-3.0/+3.0 at full scale single indicator all ranges

#### Unable To Decode:

Unable to decode or unable to decode

# Meter Depth Behind Mounting Flange:

1.081 inches

# Meter Body Diameter Behind Mounting Flange:

2.150 inches

#### Movement Type:

Moving coil, permanent magnet

#### **Background Color:**

Black single indicator all ranges and white single indicator all ranges

# Pointer Color:

White single indicator all ranges

# NSN 6625-00-604-9573

Special Scale Meter - Page 2 of 2



	ale Marking:
-	o scale 0, 5, 10, 15, 20; bottom scale 0, 0.5, 1
	unting Facility Type And Quantity:
3 so	crew and 3 unthreaded hole
Sca	ale Graduation Type:
Line	ear single indicator all ranges
Fea	atures Provided:
Ele	ctrostatic shield and magnetic shield and zero adjuster
Мо	vement Suspension Method:
Jev	vel pivot base
Cir	cuit Attachment Method And Quantity:
2 e	yelet
Spe	ecial Features:
Ruợ	ggedized
Spe	ecial Markings:
Ma	g xtal; cur cur; set mag cur; freq; flo; fb; on back, sealed do not open
Ma	terial:
Ste	el
Nu	clear Hardness Critical Feature:
Nor	nhardened
Su	rface Treatment:
Pai	nt
Spe	ecial Test Features:
Cor	mplies with mil-m-10304 and ansi specification c-39.1
Sty	le Designator:
Roi	und flush mtg
Fso	c Application Data:
Tes	st set, elect. Equip.
She	elf Life:
N/a	l de la construcción de la constru
Uni	it Of Measure:
Dei	militarization:
No	
Fiig	g:
Δ34	10a0