

View Online at <https://aerobasegroup.com/nsn/6625-00-605-0035>

**Ac Voltage Rating:**

Between 105.0 volts and 125.0 volts

**Dc Voltage Rating:**

6.300 volts

**Frequency Rating:**

Between 50.000 hertz and 125.000 hertz

**Frequency Range Rating:**

+370.0/+1000.0 megahertz

**Accessory Component Quantity:**

1 and 1 and 1 and 1 and 1 and 1 and 2 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1 and 1

**Furnished Items:**

Radio interference-field intensity meter; power supply; antenna; probe, electrical field, interference measuring; meter; case, accessories; chart set; cable assembly, special purpose; case; antenna tripod; cable assembly, radio frequency; cable assembly, special purpose; bag; cable assembly, power, electrical; cable assembly, radio frequency; mast section; headset, electrical; instruction book

**Accessory Controlling Agency:**

An; staddart aircraft radio co; navships

**Accessory Identifying Number:**

Im-52a/urm-17 type no. And pp-530a/urm-17 type no. And at-792/urm-17a type no. And dt-194/urm-17a type no. And me-131/u type no. And cy-2266/urm-17a type no. And pt-430/urm-17a type no. And 91487-1 /10 ft 0 in./ type no. And cy-866/urm-17 type no. And 10545 type no. And cg-571/u /20 ft 0 in./ type no. And cg-572/u /20 ft 0 in./ type no. And cw-219/urm-17 type no. And cx-3810/u /6 ft 60 in./ type no. And cg-92d/u /20 ft 0 in./ type no. And ab-363/u type no. And h-132/u type no. And navships 91388 type no.

**Internal Battery Accommodation:**

Not included

**Indicator Type:**

Voltmeter and aural-null

**Input Impedance Rating:**

52.0 ohms

**Frequency Band Quantity:**

1

**Frequency Channel Quantity:**

1

**Individual Channel Frequency:**

Between 370.0 megahertz and 1000.0 megahertz

**Scaleaccuracy Rating In Percent:**

+0.000/+2.000

**Scale Range:**

+0.0/+100.0 microvolts

**Frequency Calibration Accuracy Range In Percent:**

-0.200/+0.200

**Phase:**

Single

**Special Features:**

Special purpose battery cable stoddart no. 62482 to be used with battery pack when power supply pp-530a/urm-17 is not used; additional ac voltage rating: 210.000 volts min and 250.000 volts max; additional frequency rating: 50.000 hz min and 1000.000 hz max; additional dc voltage ratings: 22.500 volts and 225.000 volts

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

T228-e