## NSN 6625-00-606-7850

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-606-7850

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
1.625 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 1.306 inches and 1.318 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
Between 1.306 inches and 1.318 inches
Overall Height:
1.810 inches
Overall Width:
1.810 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
12 single indicator single range
Environmental Protection:
Shock resistant and vibration resistant and watertight
Furnished Items And Quantity:
Nut 4, screw 4, washer 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-3.0/+3.0 at full scale single indicator single range
Unable To Decode:
Unable to decode or unable to decode
Meter Depth Behind Mounting Flange:
1.000 inches
Meter Body Diameter Behind Mounting Flange:
1.510 inches

Movement Type:

Moving coil, permanent magnet

## **NSN 6625-00-606-7850** Special Scale Meter - Page 2 of 2



Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Scale Marking:
Dbv; m 45; m 30; m 15; 0; 15
Mounting Facility Type And Quantity:
4 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solderless lug
Special Features:
Ruggedized
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Special Test Features:
Meets requirements of mil-m-10304/24, type mr13w001specr
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No
Fiig:
A310a0