

View Online at <https://aerobasegroup.com/nsn/6625-00-607-3268>

Circuit Current For Which Designed:

Dc

Overall Length:

2.656 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.125 inches

Overall Height:

3.750 inches

Overall Width:

4.000 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

44 single indicator 1st range

Furnished Items And Quantity:

Terminal hardware 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

600.0 ohms per volt

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-1.5 to 1.5 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.047 inches

Meter Body Diameter Behind Mounting Flange:

2.750 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Nonlinear single indicator 2nd range

Measurement Range:

-5.0 to 15.0 decibels above or below one milliwatt single indicator 1st range

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel lusterless

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0