NSN 6625-00-607-3268

Multiple Scale Meter - Page 1 of 2

External



View Online at https://aerobasegroup.com/nsn/6625-00-607-3268

Circuit Current For Which Designed:
Dc
Overall Length:
2.656 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.375 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.125 inches
Overall Height:
3.750 inches
Overall Width:
4.000 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
44 single indicator 1st range
Furnished Items And Quantity:
Terminal hardware 2
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
600.0 ohms per volt
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-1.5 to 1.5 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
1.047 inches
Meter Body Diameter Behind Mounting Flange:
2.750 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator all ranges
Pointer Color:
Black single indicator all ranges
Power Source:

NSN 6625-00-607-3268Multiple Scale Meter - Page 2 of 2



Mounting Facility Type And Quantity:	
4 unthreaded hole	
Scale Graduation Type:	
Nonlinear single indicator 2nd range	
Measurement Range:	
5.0 to 15.0 decibels above or below one milliwatt single indicator 1st range	
Movement Suspension Method:	
Jewel pivot base	
Circuit Attachment Method And Quantity:	
2 threaded stud	
Material:	
Plastic	
Nuclear Hardness Critical Feature:	
Nonhardened	
Surface Treatment:	
Enamel lusterless	
Style Designator:	
Rectangular flush mtg	
Fsc Application Data:	
Test set, elect. Equip.	
Shelf Life:	
N/a	
Unit Of Measure:	
-	
Demilitarization:	
No	
Fiig:	
A310a0	