NSN 6625-00-607-4498

Special Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/psn/6625-00-607-4408

view Online at https://aerobasegroup.com/nsn/ooz5-00-oo/-4496
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
3000.0
Overall Length:
1.906 inches
Mounting Hole Diameter:
0.112 inches
Scale Division Quantity:
25 single indicator single range
Overall Diameter:
2.656 inches
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Mounting Bolt Circle Diameter:
2.406 inches
Furnished Items And Quantity:
Seal 1; nut 3; lockwasher 3; shield 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
5.0 milliamperes
Dial Scale Marking Color:
Black single indicator single range and green single indicator single range and red single indicator single range and yellow single indicator
single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.218 inches
Meter Body Diameter Behind Mounting Flange:

2.156 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Scale Marking:

0; .1; .2; .3; .4; .5; .7; .8; .9; dangerous; set voltage; explosive

NSN 6625-00-607-4498

Special Scale Meter - Page 2 of 2



Mounting Facility Type And Quantity:
3 screw and 3 unthreaded hole
Scale Graduation Type:
Linear single indicator single range
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 eyelet
Special Features:
Ruggedized
Special Markings:
O to .2 white band; .2 to 1 yellow marked dangerous; 1 to end of scale red marked explosive at 1; arrow marked set voltage at .6; on back,
sealed do not open
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Filg:
A310a0