

View Online at <https://aerobasegroup.com/nsn/6625-00-618-2459>

Circuit Current For Which Designed:

Dc

Reliability Indicator:

Established

Overall Length:

2.562 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.800 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

0.800 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

20 single indicator single range

Overall Diameter:

3.510 inches

Shortest Horizontal Distance Between Mounting Centers:

0.400 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud triangular

Sensitivity Rating:

20.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.281 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 1000.0 hertz single indicator single range

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 solder lug

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Electrical and electronic properties measuring and testing instruments

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0