## NSN 6625-00-618-5846

Voltmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-618-5846

Circuit Current For Which Designed:
Ac
Mounting Hole Diameter:
0.125 inches
Overall Diameter:
2.703 inches
Mounting Bolt Circle Diameter:
2.436 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Frequency Response Range:
+0.050/+1.000 kilohertz
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
2.375 inches
Meter Body Diameter Behind Mounting Flange:
Meter Body Diameter Behind Mounting Flange: 2.156 inches
2.156 inches
2.156 inches  Background Color:
2.156 inches  Background Color:  White single indicator single range
2.156 inches  Background Color:  White single indicator single range  Mounting Facility Type And Quantity:
2.156 inches  Background Color:  White single indicator single range  Mounting Facility Type And Quantity:  3 unthreaded hole
2.156 inches  Background Color:  White single indicator single range  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range:
2.156 inches  Background Color:  White single indicator single range  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0/+600.0 volts, ac single indicator single range
2.156 inches  Background Color:  White single indicator single range  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0/+600.0 volts, ac single indicator single range  Circuit Attachment Method And Quantity:
2.156 inches  Background Color:  White single indicator single range  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0/+600.0 volts, ac single indicator single range  Circuit Attachment Method And Quantity: 2 solderless lug
2.156 inches  Background Color: White single indicator single range  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+600.0 volts, ac single indicator single range  Circuit Attachment Method And Quantity: 2 solderless lug  Style Designator:
2.156 inches  Background Color: White single indicator single range  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+600.0 volts, ac single indicator single range  Circuit Attachment Method And Quantity: 2 solderless lug  Style Designator:  Round flush mtg
2.156 inches  Background Color:  White single indicator single range  Mounting Facility Type And Quantity:  3 unthreaded hole  Measurement Range: +0.0/+600.0 volts, ac single indicator single range  Circuit Attachment Method And Quantity: 2 solderless lug  Style Designator:  Round flush mtg  Shelf Life:
2.156 inches  Background Color: White single indicator single range  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+600.0 volts, ac single indicator single range  Circuit Attachment Method And Quantity: 2 solderless lug  Style Designator: Round flush mtg  Shelf Life: N/a
2.156 inches  Background Color: White single indicator single range  Mounting Facility Type And Quantity: 3 unthreaded hole  Measurement Range: +0.0/+600.0 volts, ac single indicator single range  Circuit Attachment Method And Quantity: 2 solderless lug  Style Designator: Round flush mtg  Shelf Life: N/a
2.156 inches  Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+600.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 solderless lug Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure:
2.156 inches  Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Measurement Range: +0.0/+600.0 volts, ac single indicator single range Circuit Attachment Method And Quantity: 2 solderless lug Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: