NSN 6625-00-619-3163

Voltmeter - Page 1 of 2

Dc

Overall Length:
2.220 inches
Overall Height:
2.730 inches
Overall Width:
3.150 inches

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-619-3163

| Scale Division Quantity: |
|---|
| 30 single indicator single range |
| Mounting Stud Length: |
| 0.450 inches |
| Environmental Protection: |
| Shock resistant and vibration resistant |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Furnished Items And Quantity: |
| Nut 3 |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0 to 2.0 at full scale single indicator all ranges |
| Unable To Decode: |
| Unable to decode or unable to decode |
| Meter Depth Behind Mounting Flange: |
| 1.010 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.190 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator single range |
| Pointer Color: |
| Black single indicator single range |
| Mounting Facility Type And Quantity: |
| 3 threaded stud |
| |

NSN 6625-00-619-3163 Voltmeter - Page 2 of 2



| Scale Graduation Type: |
|---|
| Linear single indicator single range |
| Measurement Range: |
| +0.0 to 150.0 volts, dc single indicator single range |
| Mounting Stud Diameter: |
| 0.112 inches |
| Features Provided: |
| Magnetic shield and zero adjuster |
| Movement Suspension Method: |
| Taut band |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Features: |
| Ruggedized |
| Material: |
| Plastic polycarbonate |
| Nuclear Hardness Critical Feature: |
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Fsc Application Data: |
| Test set, electronic equipment |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A310a0 |