NSN 6625-00-619-4166

Special Scale Meter - Page 1 of 2

Circuit Current For Which Designed:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-619-4166

1500.0
Overall Length:
7.466 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.050 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.725 inches
Overall Height:
1.520 inches
Overall Width:
6.690 inches
Scale Division Quantity:
12 single indicator single range
Mounting Stud Length:
0.500 inches
Environmental Protection:
Cold resistant and dripproof and heat resistant and shock resistant and vibration resistant
Furnished Items And Quantity:
Lamp assembly 2; mtg hdw 4; term. Hdw 4
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
20.0 milliamperes
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0/+2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
5.760 inches
Meter Body Width Behind Mounting Flange:
5.435 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range

NSN 6625-00-619-4166

Special Scale Meter - Page 2 of 2



Pointer Color:
Black single indicator single range
Scale Marking:
Psig; vacuum in hg; m 30; m 25; m 20; m 15; m 11; m 5; 0; 5; 10; 15; 20; 25; 30
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Mounting Stud Diameter:
0.190 inches
Meter Body Height Behind Mounting Flange:
1.225 inches
Features Provided:
Self-illumination facility and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
4 threaded stud
Operating Voltage Rating In Volts:
28.0 dc
Special Features:
Ruggedized
Special Markings:
Green line at m 11
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Special Test Features:
Meets requirements of mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:

Fiig:

A310a0

Demilitarization: Yes - demil/mli