## NSN 6625-00-619-4182



<b>NSN 6625-00-619-4182</b> Modulation Meter - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/6625-00-619-4182
Circuit Current For Which Designed:
Overall Length:
7.130 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
6.050 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
0.725 inches
Overall Height:
1.520 inches
Overall Width:
6.690 inches
Scale Division Quantity:
100 single indicator single range
Mounting Stud Length:
0.500 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
5.760 inches
Meter Body Width Behind Mounting Flange:
5.435 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:

+0.0 to 100.0 percent deviation single indicator single range

## NSN 6625-00-619-4182

Modulation Meter - Page 2 of 2



Mounting Stud Diameter:
0.190 inches
Meter Body Height Behind Mounting Flange:
1.240 inches
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Panel for which designed is magnetic.Circuit construction type is non-electronic.
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
-
Demilitarization:
No
Fiig:
A310a0