## NSN 6625-00-619-4340

Modulation Meter - Page 1 of 2

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-00-619-4340

Dc
Overall Length:
7.496 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
0.725 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
6.050 inches
Overall Height:
6.690 inches
Overall Width:
1.520 inches
Scale Division Quantity:
50 single indicator single range
Mounting Stud Length:
0.500 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Dial Scale Marking Color:
Black single indicator single range
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator single range
Movement Type:
Moving coil, permanent magnet
Background Color:
White single indicator single range
Pointer Color:
Black single indicator single range
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+0.0 to 100.0 percent deviation single indicator single range
Mounting Stud Diameter:

2 threaded stud

**Circuit Attachment Method And Quantity:** 

0.190 inches

## NSN 6625-00-619-4340

Modulation Meter - Page 2 of 2



Special	Features:
---------	-----------

Panel for which designed is non-magnetic. Circuit construction type is non-electronic.

**Nuclear Hardness Critical Feature:** 

Nonhardened

**Style Designator:** 

Rectangular surface mtg

**Fsc Application Data:** 

Test set, elect. Equip.

Shelf Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A310a0