

View Online at <https://aerobasegroup.com/nsn/6625-00-619-4427>

Circuit Current For Which Designed:

Dc

Overall Length:

7.496 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

0.725 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

6.050 inches

Overall Height:

6.690 inches

Overall Width:

1.520 inches

Scale Division Quantity:

100 single indicator single range

Mounting Stud Length:

0.500 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 100.0 percent deviation single indicator single range

Mounting Stud Diameter:

0.190 inches

Criticality Code Justification:

Feat

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Critical application-marine gas turbine Im 2500.Panel for which designedis non-magnetic.Circuit construction type is non-electronic.

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular surface mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0