

View Online at <https://aerobasegroup.com/nsn/6625-00-619-6935>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

2.440 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.260 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.250 inches

**Overall Height:**

2.870 inches

**Overall Width:**

4.240 inches

**Scale Division Quantity:**

15 single indicator single range

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-1.5 to 1.5 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

2.210 inches

**Meter Body Diameter Behind Mounting Flange:**

2.660 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

4 threaded stud

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 15.0 volts, ac single indicator single range

**Mounting Stud Diameter:**

0.112 inches

**Movement Suspension Method:**

Taut band

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Nuclear Hardness Critical Feature:**

Nonhardened

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0