

View Online at <https://aerobasegroup.com/nsn/6625-00-619-6954>

Circuit Current For Which Designed:

Dc

Overall Length:

2.440 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.260 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.250 inches

Overall Height:

2.870 inches

Overall Width:

4.240 inches

Scale Division Quantity:

20 single indicator single range

Mounting Stud Length:

0.500 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-1.5 to 1.5 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.210 inches

Meter Body Diameter Behind Mounting Flange:

2.660 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 2.0 volts, dc single indicator single range

Mounting Stud Diameter:

0.112 inches

Movement Suspension Method:

Taut band

Circuit Attachment Method And Quantity:

2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0