## NSN 6625-00-619-6956

Voltmeter - Page 1 of 2

**Circuit Current For Which Designed:** 



View Online at https://aerobasegroup.com/nsn/6625-00-619-6956

2.440 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
2.260 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
2.250 inches
Overall Height:
2.870 inches
Overall Width:
4.240 inches
Scale Division Quantity:
50 single indicator single range
Mounting Stud Length:
0.510 inches
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Four hole/stud rectangular/square  Dial Scale Marking Color:
-
Dial Scale Marking Color:
Dial Scale Marking Color:  Black single indicator single range
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.210 inches
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.210 inches  Meter Body Diameter Behind Mounting Flange:
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.210 inches  Meter Body Diameter Behind Mounting Flange:  2.660 inches
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 2.210 inches  Meter Body Diameter Behind Mounting Flange: 2.660 inches  Movement Type:
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.210 inches  Meter Body Diameter Behind Mounting Flange:  2.660 inches  Movement Type:  Moving coil, permanent magnet
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 2.210 inches  Meter Body Diameter Behind Mounting Flange: 2.660 inches  Movement Type:  Moving coil, permanent magnet  Background Color:
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent:  -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange:  2.210 inches  Meter Body Diameter Behind Mounting Flange:  2.660 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 2.210 inches  Meter Body Diameter Behind Mounting Flange: 2.660 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Pointer Color:
Dial Scale Marking Color:  Black single indicator single range  Accuracy In Percent: -1.5/+1.5 at full scale single indicator single range  Meter Depth Behind Mounting Flange: 2.210 inches  Meter Body Diameter Behind Mounting Flange: 2.660 inches  Movement Type:  Moving coil, permanent magnet  Background Color:  White single indicator single range  Pointer Color:  Black single indicator single range

Measurement Range:

Linear single indicator single range

+0.0/+50.0 volts, dc single indicator single range

## **NSN 6625-00-619-6956** Voltmeter - Page 2 of 2



Mounting Stud Diameter:
0.112 inches
Features Provided:
Zero adjuster
Movement Suspension Method:
Taut band
Circuit Attachment Method And Quantity:
2 threaded stud
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0