NSN 6625-00-620-4371

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-620-4371

| Mounting Type: |
|---|
| Panel |
| Overall Length: |
| 17.500 inches |
| Overall Height: |
| 13.625 inches |
| Overall Width: |
| 13.500 inches |
| Current Type: |
| Ac |
| Frequency Rating: |
| Between 50.0 hertz and 100.0 hertz |
| Case Material: |
| Aluminum |
| Case Surface Treatment: |
| Enameled |
| Frequency Range Rating: |
| +1.800/+4.000 gigahertz |
| Internal Battery Accommodation: |
| Not included |
| Output Impedance Rating: |
| 50.0 ohms |
| Voltage Rating: |
| Between 103.5 volts and 126.5 volts |
| Frequency Band Quantity: |
| 1 |
| Modulation Type: |
| Fm and pulse |
| Calibration Accuracy Rating: |
| Porm 1 pct |
| Crystal Controlled Feature: |
| Not provided |
| Calibrated Signal Output Range: |
| 200 mv to 0.1 uv |
| Signal Output Constancy: |
| Porm 20 pct maximum variation throughout freq range |
| Modulator Location: |
| Internal |
| Pulse Repetition Frequency Rating: |
| 400.0 hertz |
| Modulation Degree: |
| 100.0 percent |

NSN 6625-00-620-4371

Signal Generator - Page 2 of 2



| Phase: |
|----------------------------|
| Single |
| Functional Classification: |
| Bb-1.1 |
| Entry Date: |
| 90-10-11 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |

Fiig: T320-j