

View Online at <https://aerobasegroup.com/nsn/6625-00-620-7167>

Circuit Current For Which Designed:

Dc

Overall Length:

2.130 inches

Mounting Hole Diameter:

0.125 inches

Scale Division Quantity:

30 single indicator all ranges

Overall Diameter:

2.695 inches

Mounting Bolt Circle Diameter:

2.440 inches

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

5.0 volts

Dial Scale Marking Color:

Black single indicator all ranges

Accuracy In Percent:

-2.0/+2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.500 inches

Meter Body Diameter Behind Mounting Flange:

2.210 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator all ranges

Pointer Color:

Black single indicator all ranges

Mounting Facility Type And Quantity:

3 unthreaded hole

Scale Graduation Type:

Linear single indicator all ranges

Measurement Range:

+0.0/+300.0 milliamperes, dc single indicator 2nd range

Features Provided:

Magnetic shield

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Red arc above scale from 0.48 connected to red line on scale at 0.88, blue arc below scale connecting blue lines on scale at 120.0 and 220.0

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0