

View Online at <https://aerobasegroup.com/nsn/6625-00-625-7841>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.850 inches

Mounting Hole Diameter:

0.150 inches

Scale Division Quantity:

10 single indicator single range

Overall Diameter:

3.510 inches

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Nut 7; washer, lock 3; washer, flat 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 10.0 volts, dc single indicator single range

Features Provided:

Magnetic shield

Circuit Attachment Method And Quantity:

2 solder lug and 2 threaded stud

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Round flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0