

View Online at <https://aerobasegroup.com/nsn/6625-00-628-9215>

**Circuit Current For Which Designed:**

Ac

**Overall Length:**

4.625 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

3.375 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.375 inches

**Overall Height:**

4.297 inches

**Overall Width:**

4.297 inches

**Mounting Hole Diameter:**

0.312 inches

**Scale Division Quantity:**

75 single indicator single range

**Environmental Protection:**

Shock resistant

**Furnished Items And Quantity:**

Nut 10; washer, lock 4; washer, flat 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Sensitivity Rating:**

1.0 milliamperes

**Dial Scale Marking Color:**

Black single indicator single range

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator single range

**Meter Depth Behind Mounting Flange:**

2.969 inches

**Meter Body Diameter Behind Mounting Flange:**

3.968 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator single range

**Pointer Color:**

Black single indicator single range

**Mounting Facility Type And Quantity:**

4 screw and 4 unthreaded hole

**Scale Graduation Type:**

Linear single indicator single range

**Measurement Range:**

+0.0 to 150.0 power factor single indicator single range

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Markings:**

Calibration point green at 100 on scale

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Could comply with mil-m-16034

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, elect. Equip.

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A310a0