

View Online at <https://aerobasegroup.com/nsn/6625-00-628-9215>

Circuit Current For Which Designed:

Ac

Overall Length:

4.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.375 inches

Overall Height:

4.297 inches

Overall Width:

4.297 inches

Mounting Hole Diameter:

0.312 inches

Scale Division Quantity:

75 single indicator single range

Environmental Protection:

Shock resistant

Furnished Items And Quantity:

Nut 10; washer, lock 4; washer, flat 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

1.0 milliamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

2.969 inches

Meter Body Diameter Behind Mounting Flange:

3.968 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Mounting Facility Type And Quantity:

4 screw and 4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 150.0 power factor single indicator single range

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Markings:

Calibration point green at 100 on scale

Nuclear Hardness Critical Feature:

Nonhardened

Special Test Features:

Could comply with mil-m-16034

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A310a0