

View Online at <https://aerobasegroup.com/nsn/6625-00-633-6757>

Circuit Current For Which Designed:

Dc

Dielectric Withstanding Voltage In Volts:

1200.0

Overall Length:

2.375 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.46875 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.46875 inches

Overall Height:

3.250 inches

Overall Width:

3.250 inches

Scale Division Quantity:

40 single indicator single range

Frequency Rating:

400.0 hertz

Mounting Stud Length:

0.500 inches

Furnished Items And Quantity:

Mtg hdw 4

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Frequency Response Range:

+380.000 to 420.000 hertz

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-0.3 to 0.3 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.875 inches

Meter Body Diameter Behind Mounting Flange:

3.130 inches

Movement Type:

Electrodynamometer

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 threaded stud

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+380.0 to 420.0 hertz single indicator single range

Mounting Stud Diameter:

0.138 inches

Scale Selection Method:

Terminal

Features Provided:

Magnetic shield and zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Phase:

Single

Special Features:

Ruggedized

Material:

Steel

Nuclear Hardness Critical Feature:

Nonhardened

Surface Treatment:

Enamel

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0