Electrical Frequency Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-633-6757

To Length:

To Width:

Circuit Current For Which Designed:	
Dc	
Dielectric Withstanding Voltage In Volts:	
1200.0	
Overall Length:	
2.375 inches	
Center To Center Distance Between Mounting Facilitie	es Parallel
2.46875 inches	
Center To Center Distance Between Mounting Facilitie	es Parallel
2.46875 inches	
Overall Height:	
3.250 inches	
Overall Width:	
3.250 inches	
Scale Division Quantity:	
40 single indicator single range	
Frequency Rating:	
400.0 hertz	
Mounting Stud Length:	
0.500 inches	
Furnished Items And Quantity:	
Mtg hdw 4	
Indicator Type:	
Dial w/pointer	
Installation Design:	
Panel	
Mounting Arrangement Style:	
Four hole/stud rectangular/square	
Frequency Response Range:	
+380.000 to 420.000 hertz	
Dial Scale Marking Color:	
Black single indicator single range	
Accuracy In Percent:	
-0.3 to 0.3 at full scale single indicator single range	
Meter Depth Behind Mounting Flange:	
1.875 inches	
Meter Body Diameter Behind Mounting Flange:	
3.130 inches	
Movement Type:	
Electrodynamometer	
Background Color:	
White single indicator single range	



Pointer Color:
Black single indicator single range
Power Source:
External
Mounting Facility Type And Quantity:
4 threaded stud
Scale Graduation Type:
Linear single indicator single range
Measurement Range:
+380.0 to 420.0 hertz single indicator single range
Mounting Stud Diameter:
0.138 inches
Scale Selection Method:
Terminal
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Phase:
Single
Special Features:
Ruggedized
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A310a0