

View Online at <https://aerobasegroup.com/nsn/6625-00-635-4266>

Circuit Current For Which Designed:

Dc

Overall Length:

2.125 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.625 inches

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.312 inches

Overall Height:

3.656 inches

Overall Width:

4.266 inches

Mounting Hole Diameter:

0.156 inches

Scale Division Quantity:

6 single indicator single range

Furnished Items And Quantity:

Nut 2

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Four hole/stud rectangular/square

Sensitivity Rating:

200.0 microamperes

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-5.0 to 5.0 at full scale single indicator single range

Meter Depth Behind Mounting Flange:

1.703 inches

Meter Body Diameter Behind Mounting Flange:

2.047 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

4 unthreaded hole

Scale Graduation Type:

Linear single indicator single range

Measurement Range:

+0.0 to 30.0 percent modulation single indicator single range

Scale Selection Method:

Terminal

Features Provided:

Zero adjuster

Movement Suspension Method:

Jewel pivot base

Circuit Attachment Method And Quantity:

2 threaded stud

Special Features:

Ruggedized. Panel for which designed is non-magnetic. Circuit construction type is non-electronic.

Material:

Plastic

Nuclear Hardness Critical Feature:

Nonhardened

Style Designator:

Rectangular flush mtg

Fsc Application Data:

Test set, elect. Equip.

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiiig:

A310a0