

View Online at <https://aerobasegroup.com/nsn/6625-00-635-4304>

**Circuit Current For Which Designed:**

Ac

**Dielectric Withstanding Voltage In Volts:**

2000.0

**Overall Length:**

2.463 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

2.250 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

2.250 inches

**Overall Height:**

3.000 inches

**Overall Width:**

3.125 inches

**Mounting Hole Diameter:**

0.228 inches

**Furnished Items And Quantity:**

Nuts 4; washers 4

**Indicator Type:**

Dial w/pointer

**Installation Design:**

Panel

**Mounting Arrangement Style:**

Four hole/stud rectangular/square

**Frequency Response Range:**

+2.000 to 30.000 kilohertz

**Dial Scale Marking Color:**

Black single indicator all ranges

**Accuracy In Percent:**

-2.0 to 2.0 at full scale single indicator all ranges

**Meter Depth Behind Mounting Flange:**

1.375 inches

**Meter Body Diameter Behind Mounting Flange:**

2.750 inches

**Movement Type:**

Moving coil, permanent magnet

**Background Color:**

White single indicator all ranges

**Pointer Color:**

Black single indicator all ranges

**Power Source:**

External

**Mounting Facility Type And Quantity:**

4 unthreaded hole

**Scale Graduation Type:**

Nonlinear single indicator all ranges

**Measurement Range:**

-20.0 to 3.0 decibels single indicator 1st range

**Features Provided:**

Zero adjuster

**Movement Suspension Method:**

Jewel pivot base

**Circuit Attachment Method And Quantity:**

2 threaded stud

**Special Markings:**

Red band from 0 to 3

**Material:**

Plastic

**Nuclear Hardness Critical Feature:**

Nonhardened

**Special Test Features:**

Item meets fcc standards

**Style Designator:**

Rectangular flush mtg

**Fsc Application Data:**

Test set, electronic equipment

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A310a0