## NSN 6625-00-635-9056

Multiple Scale Meter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-635-9056

Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
1500.0
Overall Length:
2.125 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
3.604 inches
Center To Center Distance Between Mounting Facilities Parallel To Width:
3.283 inches
Overall Height:
3.933 inches
Overall Width:
4.261 inches
Mounting Hole Diameter:
0.150 inches
Scale Division Quantity:
50 single indicator 2nd range
Environmental Protection:
Airtight and dust resistant and fungus resistant and heat resistant and humidity resistant and shock resistant and vibration resistant and
water resistant
Furnished Items And Quantity:
Nut 6; lockwasher 6; seal 1
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Four hole/stud rectangular/square
Sensitivity Rating:
1.0 milliamperes
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
-2.0 to 2.0 at full scale single indicator all ranges
Meter Depth Behind Mounting Flange:
0.995 inches
Meter Body Diameter Behind Mounting Flange:
3.252 inches
Movement Type:
Moving coil, permanent magnet

White single indicator all ranges

**Background Color:** 

## NSN 6625-00-635-9056

Multiple Scale Meter - Page 2 of 2



Pointer Color:
Black single indicator all ranges
Power Source:
External
Mounting Facility Type And Quantity:
4 screw and 4 unthreaded hole
Scale Graduation Type:
Nonlinear single indicator 1st range
Measurement Range:
-10.0 to 2.0 decibels above or below one milliwatt single indicator 1st range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Features:
Ruggedized
Special Markings:
On back, made in u.S.A.
Material:
Plastic
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Paint
Special Test Features:
Complies with mil-m-10304
Style Designator:
Rectangular flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
Δ310a0