NSN 6625-00-643-0579

Voltmeter - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/6625-00-643-0579

| Circuit Current For Which Designed: |
|--|
| Ac |
| Mounting Hole Diameter: |
| 0.125 inches |
| Overall Diameter: |
| 2.695 inches |
| Mounting Bolt Circle Diameter: |
| 2.440 inches |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 1000.0 ohms per volt |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 1.751 inches |
| |
| Meter Body Diameter Behind Mounting Flange: |
| Meter Body Diameter Behind Mounting Flange: 2.210 inches |
| |
| 2.210 inches |
| 2.210 inches Background Color: |
| 2.210 inches Background Color: White single indicator single range |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Output voltage |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Output voltage Style Designator: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Output voltage Style Designator: Round flush mtg |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Output voltage Style Designator: Round flush mtg Shelf Life: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Output voltage Style Designator: Round flush mtg Shelf Life: N/a |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Output voltage Style Designator: Round flush mtg Shelf Life: N/a |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Output voltage Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: |
| 2.210 inches Background Color: White single indicator single range Mounting Facility Type And Quantity: 3 unthreaded hole Circuit Attachment Method And Quantity: 2 threaded stud Special Markings: Output voltage Style Designator: Round flush mtg Shelf Life: N/a Unit Of Measure: Demilitarization: |