NSN 6625-00-643-0601

Voltmeter - Page 1 of 2

Dc

Overall Length: 2.040 inches

0.156 inches

Mounting Hole Diameter:

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-643-0601

Scale Division Quantity:
60 single indicator all ranges
Overall Diameter:
3.500 inches
Mounting Bolt Circle Diameter:
3.160 inches
Furnished Items And Quantity:
Nut 7; washer 7
Indicator Type:
Dial w/pointer
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
5000.0 ohms per volt
Dial Scale Marking Color:
Black single indicator all ranges
Accuracy In Percent:
Accuracy In Percent: -2.0 to 2.0 at full scale single indicator all ranges
•
-2.0 to 2.0 at full scale single indicator all ranges
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange:
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange:
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type:
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type: Moving coil, permanent magnet
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type: Moving coil, permanent magnet Background Color:
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Pointer Color:
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Pointer Color: Black single indicator all ranges
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Pointer Color: Black single indicator all ranges Power Source:
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Pointer Color: Black single indicator all ranges Power Source: External
-2.0 to 2.0 at full scale single indicator all ranges Meter Depth Behind Mounting Flange: 0.970 inches Meter Body Diameter Behind Mounting Flange: 2.750 inches Movement Type: Moving coil, permanent magnet Background Color: White single indicator all ranges Pointer Color: Black single indicator all ranges Power Source: External Mounting Facility Type And Quantity:

NSN 6625-00-643-0601

Voltmeter - Page 2 of 2



Measurement Range:
+0.0 to 60.0 volts, dc single indicator 1st range
Scale Selection Method:
Terminal
Features Provided:
Zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Element voltage on dial
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Surface Treatment:
Enamel
Style Designator:
Round flush mtg
Fsc Application Data:
Test set, elect. Equip.
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

A310a0