NSN 6625-00-643-1428

Ammeter - Page 1 of 2

No



View Online at https://aerobasegroup.com/nsn/6625-00-643-1428

| Circuit Current For Which Designed: |
|---|
| Dc |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.312 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.312 inches |
| Overall Height: |
| 3.000 inches |
| Overall Width: |
| 3.000 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 50.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 1.281 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.734 inches |
| Background Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 4 threaded stud |
| Measurement Range: |
| +0.0/+10.0 milliamperes, dc single indicator 2nd range |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Style Designator: |
| Rectangular flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

NSN 6625-00-643-1428

Ammeter - Page 2 of 2



Fiig:

A310a0