NSN 6625-00-643-1468

Ammeter - Page 1 of 2

Material: Plastic

Circuit Current For Which Designed:



View Online at https://aerobasegroup.com/nsn/6625-00-643-1468

| Dc |
|---|
| Overall Length: |
| 2.468 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.250 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.250 inches |
| Overall Height: |
| 3.125 inches |
| Overall Width: |
| 3.000 inches |
| Scale Division Quantity: |
| 50 single indicator single range |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Four hole/stud rectangular/square |
| Sensitivity Rating: |
| 100.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator single range |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator single range |
| Meter Depth Behind Mounting Flange: |
| 2.343 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.760 inches |
| Background Color: |
| White single indicator single range |
| Mounting Facility Type And Quantity: |
| 4 threaded stud |
| Measurement Range: |
| +0.0/+250.0 milliamperes, dc single indicator single range |
| Mounting Stud Diameter: |
| 0.562 inches |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |

NSN 6625-00-643-1468

Ammeter - Page 2 of 2



| Nuclear Hardness Critical Feature: |
|------------------------------------|
| Nonhardened |
| Style Designator: |
| Rectangular flush mtg |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |

Fiig: A310a0