

View Online at <https://aerobasegroup.com/nsn/6625-00-643-1541>

Mounting Type:

Portable

Overall Length:

14.250 inches

Overall Height:

11.500 inches

Overall Width:

10.750 inches

Current Type:

Ac

Frequency Rating:

Between 0.05 kilohertz and 1.00 kilohertz

Case Material:

Aluminum

Case Surface Treatment:

Enameled

Frequency Range Rating:

+3.0/+405.0 megahertz

Accessory Component Quantity:

1 and 1 and 1 and 1 and 1 and 1 and 1

Accessory Controlling Agency:

Jcens

Accessory Identifying Number:

Sg-45a/urm-26 type no. And cx-1932/u type no. And cg-870/u type no. And cg-409/u type no. And cn-179/urm-26a type no. And mx-1289/urm-26a type no. And pp-644a/urm-26 type no.

Voltage Rating:

Between 103.5 volts and 126.5 volts

Frequency Band Quantity:

6

Modulation Type:

Am

Accessory Component Name:

Rf signal generator, electrical power cable, rf cable assembly, cord, fixed attenuator, test adapter, power supply

Calibration Accuracy Rating:

Porm 5 pct

Crystal Controlled Feature:

Not provided

Calibrated Signal Output Range:

0.1 microvolt to 50.0 millivolt

Signal Output Constancy:

Porm 10 pct maximum variation 3 to 100 mc; porm 20 pct maximum variation 100 to 405 mc

Modulated Frequency Rating:

Between 0.4 kilohertz and 1.0 kilohertz

Modulation Degree:

Between 0.0 percent and 60.0 percent

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

T320-j