NSN 6625-00-643-1548

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-643-1548

Porm 10 percent maximum variation throughout frequency range

Manustina Tuna.
Mounting Type:
Self-contained in case
Overall Length:
14.000 inches
Overall Height:
10.375 inches
Overall Width:
11.250 inches
Current Type:
Ac
Frequency Rating:
Between 0.0 kilohertz and 1.0 kilohertz
Case Material:
Aluminum
Case Surface Treatment:
Enameled
Frequency Range Rating:
+10.000/+50.000 kilohertz
Accessory Component Quantity:
11
Accessory Controlling Agency:
New london inst co; kings electronics
Internal Battery Accommodation:
Not included
Output Impedance Rating:
50.0 ohms
Voltage Rating:
115.0 volts
Frequency Band Quantity:
9
Modulation Type:
Am
Accessory Component Name:
Generator signal; cord; lead; dummy load electrical; adaptor; impedance matching unit; cable assembly power elec; cover
Calibration Accuracy Rating:
Porm 0.5 percent
Crystal Controlled Feature:
Not provided
Calibrated Signal Output Range:
0.1 uv to 2 v calibrated output
Signal Output Constancy:

NSN 6625-00-643-1548

Signal Generator - Page 2 of 2



Modulated	Frequency	Rating:
-----------	-----------	---------

Between 0.4 kilohertz and 1.0 kilohertz

Modulation Degree:

Between 0.0 percent and 80.0 percent

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

T320-j