# NSN 6625-00-643-1548

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-643-1548

# Mounting Type:

Self-contained in case

#### **Overall Length:**

14.000 inches

### **Overall Height:**

10.375 inches

#### **Overall Width:**

11.250 inches

#### **Current Type:**

Ac

#### **Frequency Rating:**

Between 0.0 kilohertz and 1.0 kilohertz

#### **Case Material:**

Aluminum

#### Case Surface Treatment:

Enameled

#### Frequency Range Rating:

+10.000/+50.000 kilohertz

### Accessory Component Quantity:

11

Accessory Controlling Agency:

New london inst co; kings electronics

## Internal Battery Accommodation:

Not included

#### **Output Impedance Rating:**

50.0 ohms

#### Voltage Rating:

115.0 volts

#### **Frequency Band Quantity:**

9

# Modulation Type:

Am

# Accessory Component Name:

Generator signal; cord; lead; dummy load electrical; adaptor; impedance matching unit; cable assembly power elec; cover

# **Calibration Accuracy Rating:**

Porm 0.5 percent

# Crystal Controlled Feature:

Not provided

# Calibrated Signal Output Range:

0.1 uv to 2 v calibrated output

# Signal Output Constancy:

Porm 10 percent maximum variation throughout frequency range

# NSN 6625-00-643-1548

Signal Generator - Page 2 of 2



Modulated Frequency Rating:

Between 0.4 kilohertz and 1.0 kilohertz

#### **Modulation Degree:**

Between 0.0 percent and 80.0 percent

Phase:

Single

Shelf Life:

N/a

Unit Of Measure:

---

# Demilitarization:

Yes - demil/mli

#### Fiig:

Т320-ј