## NSN 6625-00-643-1552

Signal Generator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-643-1552

| View Online at https://aerobasegroup.com/nsn/6625-00-643-1552   |
|---|
| Overall Length:   |
| 23.000 inches   |
| Overall Height:   |
| 13.000 inches   |
| Overall Width:  |
| 16.000 inches   |
| Current Type:   |
| Ac  |
| Frequency Rating:   |
| Between 0.05 kilohertz and 1.60 kilohertz   |
| Case Material:  |
| Aluminum alloy  |
| Case Surface Treatment:   |
| Enameled  |
| Frequency Range Rating:   |
| +0.020/+200.000 kilohertz   |
| Accessory Component Quantity:   |
| 1 and 1 and 1 and 1   |
| Accessory Controlling Agency:   |
| Jcens   |
| Accessory Identifying Number:   |
| An/cy-668/u type no. And an/cx-237/u type no. And an/cg-409a/u type no. And an/ug-514/u type no. And an/da-35/u type no |
| Internal Battery Accommodation:   |
| Not included  |
| Dutput Impedance Rating:  |
| 1.0 kilohms   |
| Voltage Rating:   |
| Between 105.0 volts and 117.0 volts   |
| Frequency Band Quantity:  |
| 3   |
| Accessory Component Name:   |
| Case, cord, cord, adapter-connector, dummy load   |
| Calibration Accuracy Rating:  |
| Porm 2.000 pct accuracy   |
| Crystal Controlled Feature:   |
| Not provided  |
| Calibrated Signal Output Range:   |
| 0 to 10 v   |
| Signal Output Constancy:  |
| Porm 2 db maximum variation throughout frequency range  |
| Phase:  |
|   |

Single

# NSN 6625-00-643-1552

Signal Generator - Page 2 of 2

**Functional Classification:** 

Bb-1.1

#### Entry Date:

91-01-09

Shelf Life:

N/a

## Unit Of Measure:

---

## Demilitarization:

Yes - demil/mli

Fiig:

Т320-ј

