## NSN 6625-00-643-1719

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-643-1719

Overall Length:
15.375 inches
Overall Height:
9.250 inches
Overall Width:
6.000 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 1000.0 hertz
Accessory Components And Quantity:
Book, instruction 1; cable, power 1; cover, case 1; fuse 2; leads, test 3
Voltage Rating:
Between 104.0 volts and 126.0 volts
Beam Quantity:
1
Screen Size:
3 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Frequency Range:
+3.000/+50000.000 hertz
Amplifier Deflection Sensitivity Provision:
Provided
Vertical Deflection Sensitivity Voltage Rating:
100.0 millivolts rms per inch
Horizontal Deflection Sensitivity Voltage Rating:
100.0 millivolts any acceptable outside diameter
Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Provided
Direct Connection Vertical Deflection Sensitivity Voltage Rating:
48.0 volts any acceptable outside diameter
Direct Connection Horizontal Deflection Sensitivity Voltage Rating:
67.0 volts rms per inch
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:

Between 25.0 hertz and 100000.0 hertz

## NSN 6625-00-643-1719

Oscilloscope - Page 2 of 2



Y-axis Frequency Response Rating:
Between 30.0 hertz and 2000000.0 hertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.0 megohms
Y-axis Input Impedance Rating:
1.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:

T320-g