NSN 6625-00-643-1740

Oscilloscope - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-643-1740

Overall Length:
13.500 inches
Overall Height:
9.000 inches
Overall Width:
6.000 inches
Current Type:
Ac
Frequency Rating:
Between 50.0 hertz and 1600.0 hertz
Accessory Components And Quantity:
1 cy-845u case, 1 cg-656v test lead 4 ft, 1 cg-656v test lead 1 ft, 1 hood
Voltage Rating:
Between 105.0 volts and 125.0 volts
Beam Quantity:
1
Screen Size:
3 in.
Sweep Circuits:
Included
Generator Driven Feature:
Not included
Sweep Frequency Range:
+3.000/+50000.000 hertz
Trigger Sweep Polarity Switch:
Not included
Expanded Sweep:
Not provided
Amplifier Deflection Sensitivity Provision:
Not provided
Input Intensity Modulation Feature:
Not provided
Plate Direct Connection Deflection Sensitivity Provision:
Provided
Direct Connection Vertical Deflection Sensitivity Voltage Rating:
22.0 volts any acceptable outside diameter
Direct Connection Horizontal Deflection Sensitivity Voltage Rating:
28.0 volts rms per inch
Frequency Response Rating:
Provided
X-axis Frequency Response Rating:

Between 5.0 hertz and 2000000.0 hertz

NSN 6625-00-643-1740

Oscilloscope - Page 2 of 2



Y-axis Frequency Response Rating:
Between 25.0 hertz and 100000.0 hertz
Amplifier Input Impedance Rating Provision:
Provided
X-axis Input Impedance Rating:
1.5 megohms
Y-axis Input Impedance Rating:
2.0 megohms
Calibrated Screen Scale:
Not included
Trace Storage Tube:
Not included
Camera Recording Device Accommodation:
Not provided
Phase:
Single
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiia:

T320-g