NSN 6625-00-643-1751

Voltmeter - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/6625-00-643-1751

Circuit	Current	For	Which	Designed:
---------	---------	-----	-------	-----------

Dc

Dielectric Withstanding Voltage In Volts:

3000.0

Overall Length:

2.850 inches

Mounting Hole Diameter:

Between 0.143 inches and 1.157 inches

Overall Diameter:

3.510 inches

Environmental Protection:

Shock resistant and vibration resistant and water resistant

Mounting Bolt Circle Diameter:

3.160 inches

Furnished Items And Quantity:

Lock washer 3; nut 3

Indicator Type:

Dial w/pointer

Installation Design:

Panel

Mounting Arrangement Style:

Three hole/stud bolt circle

Sensitivity Rating:

1000.0 ohms per volt

Dial Scale Marking Color:

Black single indicator single range

Accuracy In Percent:

-2.0 to 2.0 at full scale single indicator all ranges

Meter Depth Behind Mounting Flange:

1.660 inches

Meter Body Diameter Behind Mounting Flange:

2.800 inches

Movement Type:

Moving coil, permanent magnet

Background Color:

White single indicator single range

Pointer Color:

Black single indicator single range

Power Source:

External

Mounting Facility Type And Quantity:

3 screw and 3 unthreaded hole

NSN 6625-00-643-1751Voltmeter - Page 2 of 2



Scale Graduation Type:
Nonlinear single indicator single range
Measurement Range:
+0.0 to 500.0 volts, dc single indicator single range
Features Provided:
Magnetic shield and zero adjuster
Movement Suspension Method:
Jewel pivot base
Circuit Attachment Method And Quantity:
2 solder lug and 2 threaded stud
Special Features:
Ruggedizd construction, hermetically sealed
Material:
Steel
Nuclear Hardness Critical Feature:
Nonhardened
Style Designator:
Round flush mtg
Test Data Document:
81349-mil-m-10304 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-m-10304/11 government specification
Fsc Application Data:
Elec, elect. Properties measuring and test instruments
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No
Filig:
A310a0