NSN 6625-00-643-2322

Ammeter - Page 1 of 2

2000.0

Overall Length: 2.421 inches

0.150 inches

Mounting Hole Diameter:

Circuit Current For Which Designed:

Dielectric Withstanding Voltage In Volts:



View Online at https://aerobasegroup.com/nsn/6625-00-643-2322

| Scale Division Quantity: |
|---|
| 51 single indicator all ranges |
| Overall Diameter: |
| 3.500 inches |
| Mounting Bolt Circle Diameter: |
| 3.160 inches |
| Indicator Type: |
| Dial w/pointer |
| Installation Design: |
| Panel |
| Mounting Arrangement Style: |
| Three hole/stud bolt circle |
| Sensitivity Rating: |
| 250.0 millivolts |
| Dial Scale Marking Color: |
| Black single indicator all ranges |
| Accuracy In Percent: |
| -2.0/+2.0 at full scale single indicator all ranges |
| Meter Depth Behind Mounting Flange: |
| 1.660 inches |
| Meter Body Diameter Behind Mounting Flange: |
| 2.800 inches |
| Movement Type: |
| Moving coil, permanent magnet |
| Background Color: |
| White single indicator all ranges |
| Pointer Color: |
| Black single indicator all ranges |
| Mounting Facility Type And Quantity: |
| 3 unthreaded hole |
| Scale Graduation Type: |
| Linear single indicator all ranges |
| Measurement Range: |
| +0.0/+500.0 milliamperes, ac single indicator 2nd range |

NSN 6625-00-643-2322 Ammeter - Page 2 of 2



| Scale Selection Method: |
|--|
| Terminal |
| Features Provided: |
| Zero adjuster |
| Movement Suspension Method: |
| Jewel pivot base |
| Circuit Attachment Method And Quantity: |
| 2 threaded stud |
| Special Markings: |
| Caption milliamperes a.C. Center of dial below div scale |
| Material: |
| Plastic |
| Style Designator: |
| Round flush mtg |
| Fsc Application Data: |
| Test set, electronic equipment |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| Fiig: |
| A310a0 |
| |