NSN 6625-00-643-2424

Null Meter - Page 1 of 2

Material: Plastic



View Online at https://aerobasegroup.com/nsn/6625-00-643-2424

view Offilite at https://defobasegroup.com/hish/0025-00-045-2424
Circuit Current For Which Designed:
Dc
Dielectric Withstanding Voltage In Volts:
2000.0
Overall Length:
2.370 inches
Mounting Hole Diameter:
0.125 inches
Scale Division Quantity:
10 single indicator single range
Overall Diameter:
2.700 inches
Mounting Bolt Circle Diameter:
2.440 inches
Installation Design:
Panel
Mounting Arrangement Style:
Three hole/stud bolt circle
Sensitivity Rating:
500.0 microamperes
Dial Scale Marking Color:
Green and white and yellow single indicator single range
Accuracy In Percent:
-1.0 to 1.0 at full scale single indicator single range
Meter Depth Behind Mounting Flange:
1.990 inches
Meter Body Diameter Behind Mounting Flange:
2.130 inches
Movement Type:
Moving coil, permanent magnet
Background Color:
Black single indicator single range
Mounting Facility Type And Quantity:
3 unthreaded hole
Features Provided:
Portable and zero adjuster
Circuit Attachment Method And Quantity:
2 threaded stud
Special Markings:
Yellow band extends across full scale; green band in center of yellow band; white line in center of green band; pointer must fall entirely
within green zone printed below scale

NSN 6625-00-643-2424

Null Meter - Page 2 of 2



Style	Design	nator:
OLYIC	Desigi	iatoi.

Round flush mtg

Fsc Application Data:

Test set, electronic equipment

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A310a0